



TC-0153-BLA

V0

EASY Downlight recessed



Description

Downlight for indoor use.

For downlighting. Ultra-thin design. Evenly distributed light flow. Structure material: Aluminium. Structure finish: Matt white. Diffuser material: Acrylic. Diffuser finish: Opal. Warranty: 5 Years.

Finish
Matt white
Opal

Material
Aluminium
Acrylic



TECHNICAL CHARACTERISTICS

Light source

Light source: LED MLS
Output (W): 4.6W
Total power consumption (W): 5.6W
Color temperature: Neutral white - 4000K
Real Lumen: 418
Qty Leds: 30
Lm/Real W: 75
Life Time: 36.000 L70B30
Bin / Grup: 40-0A o 40-0B
UGR: 23.7

GEAR

Brand: LXD
Gear included: Yes, electronic
Voltage / Frequency:
100-240VAC/50-60Hz
Power Factor: 0.55



Luminaire





Warranty: 5 Years

Logistics

Energy Efficiency: LED A++
EAN Code: 8435381449001
Net Weight (Kg): 0.185
Weight in Kg (packaged): 0.245
Packing: 150 x 45 x 125
Masterbox: 40

The photograph may not match the reference exactly. Please read the product description to identify the finish.





ES) BLOQUE DE CONEXIÓN A RED QUE SE DEBE UTILIZAR (no incluido):
EN) MAINS TERMINAL BLOCK REQUIRED (not included):
FR) BORNIER DE RACCORDEMENT AU RESEAU REQUIS (non inclus):
DE) NOTWENDIGE VERBINDUNGSDOSE FÜR DEN NETZANSCHLUSS (nicht inklusive):

